



NO.	TYPE	COURSES	AADT (ANNUAL AVG. DAILY TRAFFIC)			
			1-600	601-1300	1301-2400	2401-4500
*①	SURFACE	ID-2 BITUMINOUS WEARING COURSE	1"	1"	1"	1"
②	SURFACE	ID-2 BITUMINOUS WEARING COURSE	1"	1"	1"	1"
**③	BASE	BITUMINOUS CONCRETE BASE COURSE	3"	5"	6"	6"
**④	SUBBASE	SUBBASE	8"	6"	6"	6"

* APPLIED 2 YEARS AFTER INITIAL PAVING

** THE SUBBASE AND THE BASE SHALL BE AT LEAST 12" WIDER THAN THE WEARING COURSES.

NOTE:

MATERIALS AND CONSTRUCTION IN ACCORDANCE WITH PA. D.O.T. FORM 408 (LATEST REVISION)

IF NECESSARY ALL UNEVEN AREAS, SETTLED AREAS, AREAS DAMAGED BY UTILITY COMPANIES AND OTHER BROKEN OR UNEVEN AREAS SHALL BE REPAIRED THEN LEVELED WITH ID-2 BITUMINOUS PRIOR TO PAVING.

PAVEMENT WIDTH IN ACCORDANCE WITH THE SUBDIVISION AND LAND DEVELOPMENT ORDINANCE.

DETAIL AND TABLE DOES NOT APPLY TO PRIVATE STREETS.

SHOULDERS TO BE EARTHEN UNLESS OTHOERWISE DIRECTED BY TOWNSHIP ENGINEER.

DISTURBED OR EXCAVATED AREAS WITHIN THREE FEET OF THE PAVEMENT EDGE AND/OR CURB MUST BE BACKFILLED WITH NO. 57 LIMESTONE TAMPED IN SIX INCH LAYERS TO THE TOTAL DEPTH OF THE DISTURBED AREA, AND CHANGING TO 3/4 INCH PER FOOT SLOPE.

Center Township Standard Detail

ROAD SECTION WITH CURBING

SD3a